SAFETY DATA SHEET

HYDRO WATERBORNE SELF-SEALER FOR INTERIORS 5 GLOSS

AF7205/00

Section 1. Identification

: HYDRO WATERBORNE SELF-SEALER FOR INTERIORS **Product name**

5 GLOSS

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Supplier's details : Wood Finishing Supplies

> LTD C/O CHEMFREIGHT 4 Bostock Place, East Tamaki, Auckland New Zealand Ph: +64 9 2733949

Mobile: +64 274 475656 www.wfsupplies.co.nz

Fx: +64 9 9749375

Manufacturer

: SHERWIN-WILLIAMS Italy S.r.I. Via del Fiffo, 12 - 40065 Pianoro (BO)

Italia - C.P. 18

Cod. Fisc. e Reg. Impr. Bo

08866930152

Emergency telephone number (with hours of operation)

: 0800 243 622 (Chemcall, Responsible Care NZ) 24

hrs./365 days

e-mail address of person responsible for this SDS

: regulatory.SWI@sherwin.

com

Section 2. Hazards identification

HSNO Classification : 6.5 - SENSITIZATION - Category B (Skin)

6.9 - SPECIFIC TARGET ORGAN TOXICITY (SINGLE OR REPEATED

EXPOSURE) - Category B

This material is classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001 and has been classified according to the Hazardous Substances (Classifications) Regulations 2001.

This material is not classified as DANGEROUS GOODS according to criteria in New Zealand Standard 5433:2012 Transport of Dangerous Goods on Land.

GHS label elements

Signal word : Warning

May cause an allergic skin reaction. **Hazard statements**

May cause damage to organs.

Precautionary statements

Prevention : Wear protective gloves. Do not breathe vapor. Do not eat, drink or smoke when

using this product. Wash hands thoroughly after handling. Contaminated work

clothing should not be allowed out of the workplace.

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs, Response

seek medical advice/attention. Wash contaminated clothing before reuse. Call a

POISON CENTER or doctor/physician if exposed or you feel unwell.

Storage : Store locked up.

Disposal Dispose of contents and container in accordance with all local, regional, national

and international regulations.

Symbol





Other hazards which do not : Please refer to the SDS for additional information. Keep out of reach of children. result in classification

Version : 3.04 Date of issue/Date of revision: 08, November, 2019 SHW-A4-AP-HSN44-NZ

HYDRO WATERBORNE SELF-SEALER FOR INTERIORS

5 GLOSS

Section 3. Composition/information on ingredients

Substance/mixture : Mixture
Other means of : Not available.

identification

CAS number/other identifiers

Product code : AF7205/00

Ingredient name	% (w/w)	CAS number
2-(2-Butoxyethoxy)-ethanol	3.2	112-34-5
2-(2-Ethoxyethoxy)-ethanol	1.5	111-90-0
2-Butoxyethanol	1.4	111-76-2
Adipohydrazide	0.5	1071-93-8

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Ingestion

: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Inhalation: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

Skin contact : May cause an allergic skin reaction.

Eye contact: No known significant effects or critical hazards.

Over-exposure signs/symptoms

Inhalation: No specific data.Ingestion: No specific data.

Version: 3.04 Date of issue/Date of revision: 08, November, 2019

SHW-A4-AP-HSN44-NZ

Page: 2/11

Section 4. First aid measures

Skin : Adverse symptoms may include the following:

> irritation redness

Eves : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Specific treatments : Not available.

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

Protection of first-aiders No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Wash contaminated clothing thoroughly with water before removing it, or wear

gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable : Use an extinguishing agent suitable for the surrounding fire.

Not suitable : None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products

: Decomposition products may include the following materials: carbon dioxide

carbon monoxide nitrogen oxides

Hazchem code

: Not available.

Special precautions for fire-

fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

: 3.04 Version Date of issue/Date of revision: 08, November, 2019

SHW-A4-AP-HSN44-NZ

Page: 3/11

Section 7. Handling and storage

Precautions for safe handling

: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits		
2-(2-Butoxyethoxy)-ethanol	ACGIH TLV (United States, 3/2018). TWA: 10 ppm 8 hours. Form: Inhalable		
	fraction and vapor		
2-Butoxyethanol	NZ HSWA 2015 (New Zealand, 11/2017).		
	Absorbed through skin.		
	WES-TWA: 25 ppm 8 hours.		
	WES-TWA: 121 mg/m ³ 8 hours.		

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Respiratory protection

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Version: 3.04 Date of issue/Date of revision: 08, November, 2019

SHW-A4-AP-HSN44-NZ

Page: 4/11

Page: 5/11

Section 8. Exposure controls/personal protection

Eye protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid.

Color : Not available. Odor : Not available. **Odor threshold** : Not available.

: 8.1 pН

: Not available. **Melting point Boiling point** : 100°C (212°F)

: Closed cup: 499°C (930.2°F) [Pensky-Martens Closed Cup] Flash point

Evaporation rate : 89 (butyl acetate = 1)

Flammability (solid, gas) : Not available. : Lower: 0.9% Lower and upper explosive Upper: 23.5% (flammable) limits

Vapor pressure : 2.3 kPa (17.5 mm Hg) [at 20°C]

Vapor density : 1 [Air = 1] : 1.04 Relative density

: Not available. Solubility Partition coefficient: n-Not available.

octanol/water

Auto-ignition temperature : Not available. : Not available. **Decomposition temperature**

Viscosity : Kinematic (40°C (104°F)): >0.205 cm²/s (>20.5 cSt)

Aerosol product

Type of aerosol : Not applicable. **Heat of combustion** : 2.194 kJ/g **lanition distance** : Not applicable. **Enclosed space ignition -**: Not applicable.

Time equivalent

Enclosed space ignition -

Deflagration density

: Not applicable.

: Not applicable. Flame height Flame duration : Not applicable.

Version : 3.04 Date of issue/Date of revision: 08, November, 2019

5 GLOSS

Section 10. Stability and reactivity

Chemical stability : The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

Incompatible materials : No specific data.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

Section 11. Toxicological information

Information on the likely routes of exposure

Inhalation : No known significant effects or critical hazards.Ingestion : No known significant effects or critical hazards.

Skin contact: May cause an allergic skin reaction.

Eye contact : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation : No specific data.
Ingestion : No specific data.

Skin contact: Adverse symptoms may include the following:

irritation redness

Eye contact : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2-(2-Butoxyethoxy)-ethanol	LD50 Dermal LD50 Oral		2700 mg/kg 4500 mg/kg	-
2-(2-Ethoxyethoxy)-ethanol 2-Butoxyethanol	LD50 Oral LCLo Inhalation Vapor LD50 Dermal LD50 Oral		7500 mg/kg >3.1 mg/l >2000 mg/kg 1300 mg/kg	- 1 hours - -

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-(2-Butoxyethoxy)-ethanol	Eyes - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
	Eyes - Severe irritant	Rabbit	_	20 milligrams	-
2-(2-Ethoxyethoxy)-ethanol	Eyes - Mild irritant	Rabbit	-	125 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	500 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
2-Butoxyethanol	Eyes - Moderate irritant	Rabbit	-	24 hours 100 milligrams	-
	Eyes - Severe irritant	Rabbit	-	100 milligrams	-
	Skin - Mild irritant	Rabbit	-	500 milligrams	-

Sensitization

Not available.

Potential chronic health effects

General : No known significant effects or critical hazards.

Version: 3.04 Date of issue/Date of revision: 08, November, 2019

SHW-A4-AP-HSN44-NZ

Page: 6/11

Page: 7/11

Section 11. Toxicological information

Inhalation

: No known significant effects or critical hazards.

Ingestion

: No known significant effects or critical hazards.

Skin contact

: Once sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

Eye contact

tact : No known significant effects or critical hazards.

Carcinogenicity

: No known significant effects or critical hazards.

Mutagenicity Teratogenicity : No known significant effects or critical hazards.

Developmental offect

: No known significant effects or critical hazards.

Developmental effects

: No known significant effects or critical hazards.

Fertility effects

No known significant effects or critical hazards.No known significant effects or critical hazards.

Chronic toxicity

Not available.

Carcinogenicity

Not available.

Mutagenicity

Not available.

Teratogenicity

Not available.

Reproductive toxicity

Not available.

Specific target organ toxicity

Name	3 3 3	Route of exposure	Target organs
2-(2-Butoxyethoxy)-ethanol	Category B	Oral Skin Inhalation	Not determined Not determined Not determined

Aspiration hazard

Not available.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	41481.36 mg/kg
Dermal	56684.55 mg/kg
Inhalation (dusts and mists)	105.53 mg/l

Section 12. Ecological information

Ecotoxicity

: No known significant effects or critical hazards.

Aquatic and terrestrial toxicity

Product/ingredient name	Result	Species	Exposure
2-(2-Butoxyethoxy)-ethanol 2-(2-Ethoxyethoxy)-ethanol	Acute LC50 1300000 μg/l Fresh water Acute LC50 3340000 μg/l Fresh water	Fish - Lepomis macrochirus Daphnia - Daphnia magna - Neonate	96 hours 48 hours
2-Butoxyethanol	Acute LC50 6010000 μg/l Fresh water Acute EC50 >1000 mg/l Fresh water Acute LC50 800000 μg/l Marine water Acute LC50 1250000 μg/l Marine water	Fish - Ictalurus punctatus Daphnia - Daphnia magna Crustaceans - Crangon crangon Fish - Menidia beryllina	96 hours 48 hours 48 hours 96 hours

Version : 3.04 Date of issue/Date of revision : 08, November, 2019

Page: 8/11

Section 12. Ecological information

Persistence/degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
2-(2-Butoxyethoxy)-ethanol 2-Butoxyethanol	-		Readily Readily

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Marine Pollutant
New Zealand Class	Not regulated.	-	-	-		No.
ADG Class	Not regulated.	-	-	-		No.
UN Class	Not regulated.	-	-	-		No.
ADR/RID Class	Not regulated.	-	-	-		No.
IATA Class	Not regulated.	-	-	-		No.
IMDG Class	Not regulated.	-	-	-		Not a pollutant.

Additional information

New Zealand Class ADG Class UN Class ADR/RID Class IATA Class IMDG Class -

PG*: Packing group

NZ NZS 14 Hazchem Code : Not available.

Version : 3.04 Date of issue/Date of revision : 08, November, 2019

HYDRO WATERBORNE SELF-SEALER FOR INTERIORS

5 GLOSS

Section 14. Transport information

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

Page: 9/11

the event of an accident or spillage.

Transport in bulk according to Annex II of MARPOL and

the IBC Code

: Not available.

Section 15. Regulatory information

HSNO Approval Number

: HSR002670

HSNO Group Standard

: Surface coatings and colourants

HSNO Classification

: 6.5 - SENSITIZATION - Category B (Skin)

6.9 - SPECIFIC TARGET ORGAN TOXICITY (SINGLE OR REPEATED

EXPOSURE) - Category B

Safety, health and environmental regulations specific for the product

: No known specific national and/or regional regulations applicable to this product

(including its ingredients).

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Section 16. Other information

History

Date of printing Date of issue/Date of

: 08, November, 2019. : 08, November, 2019

revision

Date of previous issue : 25, October, 2019

Version

3.04

Key to abbreviations

: ADG = Australian Dangerous Goods

ADR = The European Agreement concerning the International Carriage of

Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

RID = The Regulations concerning the International Carriage of Dangerous Goods

by Rail

Version : 3.04 Date of issue/Date of revision: 08, November, 2019

HYDRO WATERBORNE SELF-SEALER FOR INTERIORS
5 GLOSS

Section 16. Other information

SGG = Segregation Group UN = United Nations

References : Not available.

Indicates information that has changed from previously issued version.

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

Version: 3.04 Date of issue/Date of revision: 08, November, 2019

SHW-A4-AP-HSN44-NZ

Page: 10/11

HYDRO WATERBORNE SELF-SEALER FOR INTERIORS 5 GLOSS

Page: 11/11

Version : 3.04 Date of issue/Date of revision : 08, November, 2019 SHW-A4-AP-HSN44-NZ