

# SAFETY DATA SHEET

THINNER FOR POLYURETHANE COATINGS  
SLOW EVAPORATION

TT4131

## Section 1. Identification

**Product name** : THINNER FOR POLYURETHANE COATINGS  
SLOW EVAPORATION

**Product type** : Liquid.

**Relevant identified uses of the substance or mixture and uses advised against**

<b>Supplier's details</b>	: WOOD FINISHING SUPPLIES LTD C/O CHEMFREIGHT 4 Bostock Place, East Tamaki, Auckland, New Zealand Phone: +64 9 2733949 Fax: +64 9 9749375 Mobile: +64 274 475656 www.wfsupplies.co.nz	<b>Manufacturer</b>	: SHERWIN-WILLIAMS Italy S.r.l. Via del Fiffò, 12 - 40065 Pianoro (BO) Italia - C.P. 18 Cod. Fisc. e Reg. Impr. Bo 08866930152  Sherwin-Williams Sweden AB Box 2016, SE-195 02 Marsta SWEDEN Fax: +46 (0)381 261 99 Tel: +46 (0)381 261 00 sweden.regulatory@sherwin.com
---------------------------	--	---------------------	---

**Emergency telephone number (with hours of operation)** : 0800 243 622 (Chemcall, Responsible Care NZ) 24 hrs./365 days

**e-mail address of person responsible for this SDS** : aaroni@wfsupplies.co.nz

## Section 2. Hazards identification

**HSNO Classification** :

- 3.1 - FLAMMABLE LIQUIDS - Category C
- 6.1 - ACUTE TOXICITY (oral) - Category D
- 6.1 - ACUTE TOXICITY (dermal) - Category E
- 6.1 - ACUTE TOXICITY (inhalation) - Category D
- 6.3 - SKIN IRRITATION - Category A
- 6.4 - EYE IRRITATION - Category A (Irritant)
- 6.7 - CARCINOGENICITY - Category B
- 6.8 - REPRODUCTIVE AND DEVELOPMENTAL TOXICITY (Fertility) - Category B
- 6.8 - REPRODUCTIVE AND DEVELOPMENTAL TOXICITY (Unborn child) - Category B
- 6.9 - SPECIFIC TARGET ORGAN TOXICITY (SINGLE OR REPEATED EXPOSURE) - Category B
- 9.1 - AQUATIC ECOTOXICITY - Category D
- 9.3 - TERRESTRIAL VERTEBRATE ECOTOXICITY - Category C

This material is classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001 and has been classified according to the Hazardous Substances (Classifications) Regulations 2001.

This product is classified as DANGEROUS GOODS for transport, according to the New Zealand Standard NZS 5433: 2012 Transport of Dangerous Goods on Land.

### GHS label elements

**Signal word** : Warning

**Hazard statements** :

- Flammable liquid and vapor.
- Harmful if swallowed.
- Harmful if inhaled.
- May be harmful in contact with skin.
- Causes skin irritation.
- Causes serious eye irritation.
- Suspected of causing cancer.
- Suspected of damaging fertility or the unborn child.

**Version** : 8

**Date of issue/Date of revision** : 08, November, 2019  
SHW-A4-AP-HSN44-NZ

## Section 2. Hazards identification

May cause damage to organs.  
Harmful to aquatic life.  
Harmful to terrestrial vertebrates.

### Precautionary statements

- Prevention** : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wear protective gloves. Wear eye or face protection. Keep away from ignition sources such as heat/sparks/open flame. - No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.
- Response** : IF SWALLOWED: Rinse mouth. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Take off contaminated clothing and wash before reuse. Rinse skin with water [or shower]. Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. IF exposed or concerned: Call a POISON CENTER or doctor/physician if exposed or you feel unwell. Get medical advice/attention.
- Storage** : Store locked up. Store in cool/well-ventilated place.
- Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Symbol** :



**Other hazards which do not result in classification** : Please refer to the SDS for additional information. Keep out of reach of children.

## Section 3. Composition/information on ingredients

- Substance/mixture** : Mixture
- Other means of identification** : Not available.
- CAS number/other identifiers**
- Product code** : TT4131

Ingredient name	% (w/w)	CAS number
n-Butyl Acetate	46.0	123-86-4
Xylene, mixed isomers	37.3	1330-20-7
2-methoxy-1-methylethyl acetate	10.0	108-65-6
Ethylbenzene	6.6	100-41-4

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.**

Occupational exposure limits, if available, are listed in Section 8.

## **Section 4. First aid measures**

### Description of necessary first aid measures

- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Inhalation** : Harmful if inhaled.
- Ingestion** : Harmful if swallowed.
- Skin contact** : May be harmful in contact with skin. Causes skin irritation.
- Eye contact** : Causes serious eye irritation.

#### Over-exposure signs/symptoms

- Inhalation** : Adverse symptoms may include the following:  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Skin** : Adverse symptoms may include the following:  
irritation  
redness  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Eyes** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

### Indication of immediate medical attention and special treatment needed, if necessary

- Specific treatments** : Not available.
- Notes to physician** : No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

## Section 4. First aid measures

- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### Extinguishing media

- Suitable** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

- Not suitable** : Do not use water jet.

- Specific hazards arising from the chemical** : Flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard. This material is harmful to aquatic life. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide

- Hazchem code** : Not available.

- Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

- Personal precautions, protective equipment and emergency procedures** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.

- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

- Precautions for safe handling** : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

Ingredient name	Exposure limits
n-Butyl Acetate	<b>NZ HSWA 2015 (New Zealand, 11/2017).</b> WES-TWA: 150 ppm 8 hours. WES-TWA: 713 mg/m <sup>3</sup> 8 hours. WES-STEL: 950 mg/m <sup>3</sup> 15 minutes. WES-STEL: 200 ppm 15 minutes.
Xylene, mixed isomers	<b>NZ HSWA 2015 (New Zealand, 11/2017).</b> WES-TWA: 50 ppm 8 hours. WES-TWA: 217 mg/m <sup>3</sup> 8 hours.
2-methoxy-1-methylethyl acetate	<b>EH40/2005 WELs (United Kingdom (UK), 8/2018). Absorbed through skin.</b> STEL: 548 mg/m <sup>3</sup> 15 minutes. TWA: 50 ppm 8 hours. TWA: 274 mg/m <sup>3</sup> 8 hours. STEL: 100 ppm 15 minutes.
Ethylbenzene	<b>NZ HSWA 2015 (New Zealand, 11/2017).</b> WES-TWA: 100 ppm 8 hours. WES-TWA: 434 mg/m <sup>3</sup> 8 hours. WES-STEL: 543 mg/m <sup>3</sup> 15 minutes. WES-STEL: 125 ppm 15 minutes.

- Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

## **Section 8. Exposure controls/personal protection**

- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
- Individual protection measures**
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Respiratory protection** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Eye protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
- Skin protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

## **Section 9. Physical and chemical properties**

### **Appearance**

- Physical state** : Liquid.
- Color** : Not available.
- Odor** : Not available.
- Odor threshold** : Not available.
- pH** : Not available.
- Melting point** : Not available.
- Boiling point** : 123°C (253.4°F)
- Flash point** : Closed cup: 24°C (75.2°F) [Pensky-Martens Closed Cup]
- Evaporation rate** : 1 (butyl acetate = 1)
- Flammability (solid, gas)** : Not available.
- Lower and upper explosive (flammable) limits** : Lower: 1%  
Upper: 13.1%
- Vapor pressure** : 1.3 kPa (10 mm Hg) [at 20°C]
- Vapor density** : 3.66 [Air = 1]
- Relative density** : 0.88
- Solubility** : Not available.
- Partition coefficient: n-octanol/water** : Not available.
- Auto-ignition temperature** : Not available.



## Section 9. Physical and chemical properties

<b>Decomposition temperature</b>	: Not available.
<b>Viscosity</b>	: Kinematic (40°C (104°F)): <0.205 cm <sup>2</sup> /s (<20.5 cSt)
<b>Aerosol product</b>	
<b>Type of aerosol</b>	: Not applicable.
<b>Heat of combustion</b>	: 27.948 kJ/g
<b>Ignition distance</b>	: Not applicable.
<b>Enclosed space ignition - Time equivalent</b>	: Not applicable.
<b>Enclosed space ignition - Deflagration density</b>	: Not applicable.
<b>Flame height</b>	: Not applicable.
<b>Flame duration</b>	: Not applicable.

## Section 10. Stability and reactivity

<b>Chemical stability</b>	: The product is stable.
<b>Possibility of hazardous reactions</b>	: Under normal conditions of storage and use, hazardous reactions will not occur.
<b>Conditions to avoid</b>	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.
<b>Incompatible materials</b>	: Reactive or incompatible with the following materials: oxidizing materials
<b>Hazardous decomposition products</b>	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### Information on the likely routes of exposure

<b>Inhalation</b>	: Harmful if inhaled.
<b>Ingestion</b>	: Harmful if swallowed.
<b>Skin contact</b>	: May be harmful in contact with skin. Causes skin irritation.
<b>Eye contact</b>	: Causes serious eye irritation.

### Symptoms related to the physical, chemical and toxicological characteristics

<b>Inhalation</b>	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
<b>Ingestion</b>	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
<b>Skin contact</b>	: Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations
<b>Eye contact</b>	: Adverse symptoms may include the following: pain or irritation watering redness

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Acute toxicity

## Section 11. Toxicological information

Product/ingredient name	Result	Species	Dose	Exposure
n-Butyl Acetate	LD50 Dermal	Rabbit	>17600 mg/kg	-
	LD50 Oral	Rat	10768 mg/kg	-
Xylene, mixed isomers	LC50 Inhalation Gas.	Rat	5000 ppm	4 hours
	LD50 Oral	Rat	4300 mg/kg	-
2-methoxy-1-methylethyl acetate	LD50 Dermal	Rabbit	>5 g/kg	-
	LD50 Oral	Rat	8532 mg/kg	-
Ethylbenzene	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	3500 mg/kg	-

### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
n-Butyl Acetate	Eyes - Moderate irritant	Rabbit	-	100 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-
Xylene, mixed isomers	Eyes - Mild irritant	Rabbit	-	87 milligrams	-
	Eyes - Severe irritant	Rabbit	-	24 hours 5 milligrams	-
	Skin - Mild irritant	Rat	-	8 hours 60 microliters	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-
Ethylbenzene	Skin - Moderate irritant	Rabbit	-	100 Percent	-
	Eyes - Severe irritant	Rabbit	-	500 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 15 milligrams	-

### Sensitization

Not available.

### Potential chronic health effects

**General** : No known significant effects or critical hazards.

**Inhalation** : No known significant effects or critical hazards.

**Ingestion** : No known significant effects or critical hazards.

**Skin contact** : No known significant effects or critical hazards.

**Eye contact** : No known significant effects or critical hazards.

**Carcinogenicity** : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.

**Mutagenicity** : No known significant effects or critical hazards.

**Teratogenicity** : Suspected of damaging the unborn child.

**Developmental effects** : No known significant effects or critical hazards.

**Fertility effects** : Suspected of damaging fertility.

### Chronic toxicity

Not available.

### Carcinogenicity

Not available.

### Mutagenicity

Not available.

### Teratogenicity

Not available.



## Section 11. Toxicological information

### Reproductive toxicity

Not available.

### Specific target organ toxicity

Name	Category	Route of exposure	Target organs
Xylene, mixed isomers	Category B	Oral Inhalation	Not determined Not determined
Ethylbenzene	Category B	Inhalation	Not determined

### Aspiration hazard

Not available.

### Numerical measures of toxicity

#### Acute toxicity estimates

Route	ATE value
Oral	1053.05 mg/kg
Dermal	2946.03 mg/kg
Inhalation (vapors)	166.67 mg/l
Inhalation (dusts and mists)	3.26 mg/l

## Section 12. Ecological information

**Ecotoxicity** : This material is harmful to aquatic life.

### Aquatic and terrestrial toxicity

Product/ingredient name	Result	Species	Exposure
n-Butyl Acetate	Acute LC50 32 mg/l Marine water	Crustaceans - Artemia salina	48 hours
Xylene, mixed isomers	Acute LC50 18000 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute LC50 8500 µg/l Marine water	Crustaceans - Palaemonetes pugio	48 hours
Ethylbenzene	Acute LC50 13400 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute EC50 4600 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 3600 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Acute EC50 6.53 mg/l Marine water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute EC50 2.93 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 4200 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours

### Persistence/degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
n-Butyl Acetate	-	-	Readily
Xylene, mixed isomers	-	-	Readily
Ethylbenzene	-	-	Readily

### Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Xylene, mixed isomers	-	8.1 to 25.9	low

### Mobility in soil







**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Other adverse effects** : No known significant effects or critical hazards.

## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Marine Pollutant
New Zealand Class	UN1263	PAINT RELATED MATERIAL	3	III		No.
ADG Class	UN1263	PAINT RELATED MATERIAL	3	III		No.
UN Class	UN1263	PAINT RELATED MATERIAL	3	III		No.
ADR/RID Class	UN1263	PAINT RELATED MATERIAL	3	III		No.
IATA Class	UN1263	PAINT RELATED MATERIAL	3	III		No.
IMDG Class	UN1263	PAINT RELATED MATERIAL	3	III		Not a pollutant.

### Additional information

New Zealand Class -  
 ADG Class -  
 UN Class -  
 ADR/RID Class **Tunnel code** D/E  
 IATA Class -  
 IMDG Class **Emergency schedules** F-E, S-E

PG\* : Packing group

NZ NZS 14 Hazchem Code : Not available.

## Section 14. Transport information

**Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Transport in bulk according to Annex II of MARPOL and the IBC Code** : Not available.

## Section 15. Regulatory information

**HSNO Approval Number** : HSR002502

**HSNO Group Standard** : Additives, process chemicals and raw materials

**HSNO Classification** : 3.1 - FLAMMABLE LIQUIDS - Category C  
6.1 - ACUTE TOXICITY (oral) - Category D  
6.1 - ACUTE TOXICITY (dermal) - Category E  
6.1 - ACUTE TOXICITY (inhalation) - Category D  
6.3 - SKIN IRRITATION - Category A  
6.4 - EYE IRRITATION - Category A (Irritant)  
6.7 - CARCINOGENICITY - Category B  
6.8 - REPRODUCTIVE AND DEVELOPMENTAL TOXICITY (Fertility) - Category B  
6.8 - REPRODUCTIVE AND DEVELOPMENTAL TOXICITY (Unborn child) - Category B  
6.9 - SPECIFIC TARGET ORGAN TOXICITY (SINGLE OR REPEATED EXPOSURE) - Category B  
9.1 - AQUATIC ECOTOXICITY - Category D  
9.3 - TERRESTRIAL VERTEBRATE ECOTOXICITY - Category C

**Safety, health and environmental regulations specific for the product** : No known specific national and/or regional regulations applicable to this product (including its ingredients).

### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

## Section 16. Other information

### History

**Date of printing** : 08, November, 2019.

**Date of issue/Date of revision** : 08, November, 2019

**Date of previous issue** : 21, May, 2019

**Version** : 8

## **Section 16. Other information**

**Key to abbreviations** : ADG = Australian Dangerous Goods  
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road  
ATE = Acute Toxicity Estimate  
BCF = Bioconcentration Factor  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail  
SGG = Segregation Group  
UN = United Nations

**References** : Not available.

✔ Indicates information that has changed from previously issued version.

### **Notice to reader**

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

